Delock Adapter USB Type-C[™] male > Displayport female (DP Alt Mode) 4K 60 Hz

Description

This Delock adapter is suitable for the connection of a Displayport monitor to a computer with USB-C[™] interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like the Macbook, Chromebook and similar. In addition, the adapter can also operate on a Thunderbolt[™] 3 interface.

Specification

- Connector: USB Type-C[™] male > Displayport 20 pin female
- Chipset: ST 042K46
- Displayport 1.2 specification
- Resolution up to 4096 x 2160 @ 60 Hz
- (depending on the system and the connected hardware) • Transfer of audio and video signals
- USB bus powered
- Plug & Play
- Gold-plated connector
- 1 x ferrite core
- Cable length without connector: ca. 20 cm
- Colour: black

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Mac OS 10.9
- PC or laptop with a free USB Type-C[™] port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt[™] 3 port

Package content

USB-C[™] to Displayport Adapter

Images



Item No. 62727

EAN: 4043619627271

Country of origin: China

Package: Retail Box







4K 60Hz





| General | |
|-----------------------------|-------------------------------|
| Funktion: | Plug & Play |
| Specification: | Displayport 1.2 |
| Supported operating system: | Mac 10.9 |
| | Windows 7 32-bit |
| | Windows 7 64-bit |
| | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 32-bit |
| | Windows 10 64-bit |
| | Windows 10 Mobile |
| Interface | |
| Input: | 1 x USB Type-C™ male |
| Output: | 1 x Displayport 20 pin female |
| Technical characteristics | |
| Chipset: | ST 042K46 |
| Maximum screen resolution: | 4096 x 2160 @ 60 Hz |
| Signal transmission: | video |
| | audio |
| Physical characteristics | |
| Ferrite core: | 1 x |
| Cable length: | 20 cm |
| Connector finishing: | gold-plated |
| Colour: | black |