

Delock Cable Displayport 1.2 male > Displayport female panel-mount 1 m

Description

This cable enables you to extend a Displayport connection and can be used to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. This can be used to install an Displayport connector at an easily accessible position.



Specification

- Connector:
Displayport 20 pin male >
Displayport 20 pin female with screw nuts for installation
- Screw type: #4-40 UNC
- Mounting hole ca. 18 x 7 mm, screw hole pitch ca. 27 mm
- Displayport 1.2 specification
- Pin 20 is connected (supports 3.3 V)
- Supports a resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Gold-plated connector
- Colour: black
- Length incl. connector: ca. 100 cm

System requirements

- A free Displayport port

Package content

- Displayport panel-mount cable
- 2 screws

Item No. 85114

EAN: 4043619851140

Country of origin: China

Package: Poly bag



Images



General	
Specification:	Displayport 1.2
Interface	
Connection 1:	1 x Displayport 20 pin male
Connection 2:	1 x Displayport 20 pin female for installation
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Cable diameter:	6 mm
Conductor gauge:	30 AWG
Colour:	black
Length:	100 cm