

# Delock WLAN Antenna 802.11 ac/a/b/g/n RP-SMA 5 dBi omnidirectional joint

## Description

This WLAN antenna is designed to be connected to devices with RP-SMA interface, in order to send and receive WLAN dual band signals.



RP-SMA

## Specification

- Connector: RP-SMA plug
- With flexible joint, rotatable
- Frequency range:
  - 2.4000 ~ 2.4835 GHz
  - 5.1500 ~ 5.7250 GHz
- Impedance: 50 Ohm
- Antenna gain: 5 dBi
- VSWR: 2.0 max.
- Operating temperature: -20 °C ~ 65 °C
- Length:
  - with flexible joint: ca. 195 mm
  - without flexible joint: ca. 165 mm
- Diameter:
  - peak: ca. 6 mm
  - RP-SMA: ca. 12.5 mm

## System requirements

- Device with RP-SMA connector

## Package content

- WLAN antenna RP-SMA





## Item No. 88393

EAN: 4043619883936

Country of origin: Taiwan, Republic of China

Package: Poly bag

Images



General	
Suitable for indoor:	yes
Operating temperature:	-20 °C ~ 65 °C
Interface	
Connection:	RP-SMA plug
Technical characteristics	
Frequency range:	5.1500 GHz - 5.7250 GHz 2.4000 GHz - 2.4835 GHz
Gain:	5 dBi
Horizontal beam form:	360°
Impedance:	50 Ohm
Polarisation:	linear vertical
VSWR:	2
Physical characteristics	
Housing colour:	black
Diameter:	12.5 cm
Housing:	TPEE
Length:	19.6 cm