

Delock LTE Antenna RP-SMA -0.9 ~ 2.3 dBi Omnidirectional With Flexible Joint

Description

This GSM/UMTS/LTE antenna can be connected to your GSM/UMTS/LTE device with RP-SMA connector in order to receive or to send a signal.



RP-SMA

Specification

- RP-SMA male screw interface
- With flexible joint, rotatable
- Frequency range/ gain: 790 ~ 870 MHz, -0.9 ~ 0.6 dBi,
1710 ~ 1880 MHz, 0.7 ~ 1.8 dBi,
1920 ~ 2170 MHz, 1.3 ~ 1.9 dBi,
2500 ~ 2700 MHz, 0.9 ~ 2.3 dBi
- LTE band 1/3/7/9/20
- GSM1800/UMTS/
- VSWR: 4.0 : 1 Max.
- Polarization: linear, vertical
- Impedance: 50 Ohm
- ABS UV resistant
- Operating temperature: -10 °C ~ 55 °C
- Dimension: with flexible joint 197.10 mm
without flexible joint 167.00 mm
- Ø: 25.40 mm (top)
28.00 mm (body)
13.50 mm (base)

Item No. 88428

EAN: 4043619884285

Country of origin: Taiwan, Republic of China

Package: Poly bag

Package content

- LTE RP-SMA antenna

Images

