

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® C277 – 2x4,00 mm<sup>2</sup>

### Flexible Double Density Sheath Speaker Cable



A	B	C	D
---	---	---	---

**CATEGORY** Flexible Speaker Cable (See Audio Catalogue)  
**APPLICATIONS** Professional Loudspeakers and premade cables

- A:** First Soft **PVC** Sheath. Available in different color.  
Outer cable Diam. Ø 10,80 (±0,20) mm.
- B:** Second Soft **PVC** Sheath with different density.
- C:** Core Insulation with a Third PVC Sheath, colored one Red and one Black.  
Diam. Ø 4,20 (±0,20) mm.
- D:** O.F.C. red copper formation 120x0,20 mm.  
Nom. Cross section 2x4,00 mm<sup>2</sup>.

**MARKING** tasker® C277 2x4.00 - 11 AWG – O.F.C. Loudspeaker Cable – Italy  
**CUSTOM** This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,  
**PRODUCTION** with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	4,31 Ω/Km
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			