



Delock External Enclosure 2 x M.2 Key B SSD > USB 3.1 Gen 2 USB Type- C^{TM} female with RAID

Description

The aluminium enclosure by Delock enables the installation of two M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop. When using more than one SSD, there is the possibility to use different RAID level.



Specification

Connectors:

external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female internal: 2 x 67 pin M.2 key B slot

- Chipset: Asmedia ASM1352R
- Supports M.2 modules in format 2280, 2260 and 2242 with key B based on SATA
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Data transfer rate up to 6 Gbps
- · Supports RAID 0, RAID 1, JBOD, Port Multiplier
- LED indicator for RAID mode
- 1 x button for RAID setting
- Compliant with USB Attached SCSI Protocol (UASP) Rev. 1.0
- · Hot Plug, Plug & Play
- Colour: grey
- Dimensions (LxWxH): ca. 125 x 77 x 15.5 mm

System requirements

- Linux Kernel 4.2 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- · External enclosure
- Screws
- Cable USB-C™ male to USB Type-A male, length ca. 50 cm
- User manual

Images







Item no. 42589

EAN: 4043619425891

Country of origin: China

Package: Retail Box







| Function: Hot Plug & Play Supported operating system: Linux Kernel 4.2 or above Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 1.0 32-bit Windows 1.0 32-bit Windows 1.0 32-bit Windows 1.0 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on 1.5 mm application of double-sided assembled modules supported the module: The module | General | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------------------------------------------------------------------|
| Supported operating system: Linux Kernel 4.2 or above Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 64-bit Maximum height of the components on the module: Interface External: Interface External: Internal: 2 x 67 pin M.2 key B slot Technical characteristics Pala transfer rate: 6 Gb/s RAID function: JBOD 0 1 port Multiplier Physical characteristics Housing material: Length: Aluminium Length: Vidth: 77 mm Height: 1.5 may application of double-sided assembled modules supported Here assembled modules supported Technical characteristics 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female 2 x 67 pin M.2 key B slot Technical characteristics Aluminium Length: Vidth: 77 mm Height: 1.5 mm | Function: | Hot Plug |
| Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: Vidth: 77 mm Height: 15.5 mm | | Plug & Play |
| Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | Supported operating system: | Linux Kernel 4.2 or above |
| Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: Width: 77 mm Height: 15.5 mm | | Mac OS 10.9 or above |
| Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD O 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: Vidth: 77 mm Height: 15.5 mm | | Windows 7 32-bit |
| Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 port Multiplier Physical characteristics Housing material: Aluminium Length: Vidth: 77 mm Height: 15.5 mm | | Windows 7 64-bit |
| Windows 10 32-bit Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | Windows 8.1 32-bit |
| Windows 10 64-bit Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | Windows 8.1 64-bit |
| Supported module: M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA Maximum height of the components on the module: Interface External: Internal: Internal | | Windows 10 32-bit |
| Maximum height of the components on the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | Windows 10 64-bit |
| the module: Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | Supported module: | M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA |
| Interface External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | Maximum height of the components on | 1.5 mm application of double-sided assembled modules supported |
| External: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | the module: | |
| Internal: 2 x 67 pin M.2 key B slot Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Length: 125 mm Width: 77 mm Height: 15.5 mm | Interface | |
| Technical characteristics Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | External: | 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female |
| Data transfer rate: 6 Gb/s RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | Internal: | 2 x 67 pin M.2 key B slot |
| RAID function: JBOD 0 1 Port Multiplier Physical characteristics Housing material: Length: 125 mm Width: 77 mm Height: 15.5 mm | Technical characteristics | |
| 0 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | Data transfer rate: | 6 Gb/s |
| 1 Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | RAID function: | JBOD |
| Port Multiplier Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | 0 |
| Physical characteristics Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | 1 |
| Housing material: Aluminium Length: 125 mm Width: 77 mm Height: 15.5 mm | | Port Multiplier |
| Length: 125 mm Width: 77 mm Height: 15.5 mm | Physical characteristics | |
| Width: 77 mm Height: 15.5 mm | Housing material: | Aluminium |
| Height: 15.5 mm | Length: | 125 mm |
| | Width: | 77 mm |
| Colour: grey | Height: | 15.5 mm |
| | Colour: | grey |