

# Delock Adapter USB 2.0 Type-A > 1 x Serial DB9 RS-232

## Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.



ca. 0,8 m

## Specification

- Connectors:  
 1 x USB 2.0 Type-A male >  
 1 x serial RS-232 DB9 male with screws
- Chipset: FTDI
- Data transfer rate up to 460.8 Kbps
- Cable length incl. connectors: ca. 0.8 m

## System requirements

- Linux Kernel 2.4 or above
- Mac OS 10.5 or above
- Windows Server 2008/Server 2008-64
- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 1 x serial adapter
- USB 2.0 extension cable
- Driver CD
- User manual

## Item no. 61425


EAN: 4043619614257

Country of origin: China

Package: Retail Box



## Images



**General**

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows Server 2008 R2 Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Linux Kernel 2.6 or above

**Interface**

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 male

**Technical characteristics**

Chipset:	FTDI FT232RL
FIFO:	128 byte 256 Byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Current consumption:	20 mA

**Physical characteristics**

Cable colour:	transparent
Cable length:	80 cm
Cable length incl. connector:	87 cm
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double
Colour:	black